

T-140 AK

40 bar (600 psi) 钢丝编织



内胶层:黑色SBR -耐油雾

加强层:高强度钢丝编织

外胶层:黄色SBR -耐磨损、耐臭氧、耐烃类化合物-刺孔工艺

应用:高压空气, 适合恶劣工况(矿山、采石场), 具有更久的使用寿命和更高的安全系数

安全系数: 4:1

温度范围: -30 °C +80 °C (-22 °F +176 °F)

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
140AK013251X03	13	1/2	25	6	650	40	600		65	15,25/30,5	30,5
140AK019311X03	19	3/4	31	6	810	40	600		95	15,25/30,5	30,5
140AK025371X03	25	1	37	6	1010	40	600		125	15,25/30,5	30,5
140AK032441X03	32	1 1/4	44	6	1240	40	600		160	15,25/30,5	30,5
140AK038521X03	38	1 1/2	52	7	1660	40	600		190	15,25/30,5	30,5
140AK051651X03	51	2	65	7	2350	40	600		255	15,25/30,5	30,5
140AK063831X03	63	2 1/2	83	10	3570	30	450		315	15,25/30,5	30,5
140AK076961X03	76	3	96	10	4260	30	450		380	15,25/30,5	30,5
140AK102221X03	102	4	122	10	6150	30	450		510	15,25/30,5	30,5