

L-186 AA

压缩空气 20 bar (300 psi)

- 恶劣工况



内胶层:黑色合成橡胶 – 耐油雾

加强层:高强度纤维线

外胶层:黑色合成橡胶 – 耐磨损、耐臭氧

应用:压缩空气及一般工业用途

安全系数: 3:1

温度范围:-10 °C +60 °C (-14 °F +140 °F)

Code	ID mm	ID inch	OD mm	Wall min	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
186AA005111QI0	5	3/16	10	2,5	90	20	300		40	100	100
186AA006141QI0	6	1/4	14	4	170	20	300		48	100	100
186AA008171QI0	8	5/16	17	4,5	240	20	300		64	100	100
186AA010191QI0	10	3/8	19	4,5	280	20	300		80	100	100
186AA013231QI0	13	1/2	23	5	385	20	300		104	100	100
186AA014231QI0	14	9/16	23	4,5	335	20	300		112	100	100
186AA016261QI0	16	5/8	26	5	420	20	300		128	100	100
186AA019301QI0	19	3/4	30	5,5	540	20	300		152	50/100	50/100
186AA025371QI0	25	1	37	6	730	20	300		200	50/100	50/100