

S-174 BB

通风管 - 耐高温 +100°C (+212 °F)

UL 94 V0



结构: 纤维编织 表面阻燃 PVC

加强层: 螺旋钢丝

应用: 抽取热空气, 烟尘等气体。空调 - 通风管道

温度范围: -20 °C +100 °C (-4 °F +212 °F)

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
174BB040000000	40	1 9/16			110				20	10	10
174BB051000000	51	2			120				25	10	10
174BB060000000	60	2 3/8			140				30	10	10
174BB070000000	70	2 3/4			160				35	10	10
174BB076000000	76	3			180				40	10	10
174BB080000000	80	3 1/8			200				40	10	10
174BB090000000	90	3 9/16			215				45	10	10
174BB102000000	102	4			240				50	10	10
174BB120000000	120	4 3/4			300				60	10	10
174BB127000000	127	5			320				63	10	10
174BB140000000	140	5 1/2			350				70	10	10
174BB152000000	152	6			370				75	10	10
174BB160000000	160	6 5/16			440				80	10	10
174BB180000000	180	7 1/16			540				90	10	10
174BB203000000	203	8			600				100	10	10
174BB254000000	254	10			790				125	10	10
174BB305000000	305	12			950				150	10	10