

H-178 AA
通风管 - 耐高温 +120°C (+248°F)



结构: 完全可回收的黑色EPDM/PP，不含卤素和邻苯二甲酸盐
加强层: 螺旋钢丝
应用: 抽取热空气，烟尘等气体。耐热性好
温度范围: -40°C +120°C (-40 °F +248 °F)

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
178AA040000000					180			20	34	20	20
178AA051000000					230			20	43	20	20
178AA060000000					260			20	51	20	20
178AA063000000					280			20	54	20	20
178AA070000000					430			20	60	20	20
178AA076000000					470			20	65	20	20
178AA080000000					490			20	68	20	20
178AA090000000					550			20	77	20	20
178AA102000000					610			15	102	15	15
178AA110000000					650			15	94	15	15
178AA120000000					710			10	102	15	15
178AA127000000					770			10	108	15	15
178AA140000000					860			10	119	15	15
178AA152000000					930			10	129	15	15
178AA160000000					1030			10	136	15	15
178AA180000000					1310			5	153	15	15
178AA203000000					1470			5	173	15	15
178AA254000000					1950			5	216	10	10
178AA305000000					2380			5	259	10	10
178AA356000000					2770			5	303	10	
178AA406000000					3150			5	345	10	