

T-340 AH

蒸气管 18 bar (270 psi) 钢丝编织

NFT 47263 CAT I TYPE 3

BS 5342/2 CLASS A DIN 2825



内胶层:黑色导电EPDM

加强层:两层高强度钢丝编织

外胶层:红色EPDM -耐热、耐磨损、耐臭氧-刺孔工艺

应用:饱和或过热水蒸气

安全系数: 10:1

温度范围: -40 °C +210 °C (-40 °F +410 °F)

瞬间可承受最高温度232 °C (450 °F)

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
340AH010223YA3	10	3/8	22	6	510	18	270		100	61	61
340AH013253YA3	13	1/2	25	6	580	18	270		130	15,25/30,5/61	30,5
340AH016283YA3	16	5/8	28	6	640	18	270		160	61	61
340AH019323YA3	19	3/4	32	6,5	750	18	270		190	15,25/30,5/61	61
340AH019333YA3	19	3/4	33	7	870	18	270		190	61	
340AH025383YA3	25	1	38	6,5	940	18	270		250	15,25/30,5/61	61
340AH025403YA3	25	1	40	7,5	1080	18	270		250	61	
340AH032463YA3	32	1 1/4	46	7	1390	18	270		320	61	61
340AH032483YA3	32	1 1/4	48	8	1560	18	270		320	61	
340AH038523YA3	38	1 1/2	52	7	1610	18	270		380	61	61
340AH038543YA3	38	1 1/2	54	8	1810	18	270		380	61	
340AH051673YA3	51	2	67	8	2240	18	270		510	61	61
340AH051693YA3	51	2	69	9	2490	18	270		510	61	
340AH063833YA3	63	2 1/2	83	10	3830	18	270		630	30,5	30,5
340AH076963YA3	76	3	96	10	4540	18	270		760	30,5	30,5