

T-352 AA

散热器管 5 bar-优于 DIN 73411

SAE 20R1 D-2



内胶层:黑色EPDM

加强层:高强度纤维线

外胶层:黑色EPDM -耐热、耐磨损、耐臭氧

应用:散热器

安全系数: 3:1

温度范围: -40 ° C +120 ° C (-40 ° F +248 ° F)

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Available Length m	Stock Length m
352AA013213WD0	13	1/2	21	4	290	5	75	1/61	61
352AA016243WD0	16	5/8	24	4	330	5	75	1/61	61
352AA018263WD0	18	11/16	26	4	360	5	75	1/61	61
352AA020283WD0	20	13/16	28	4	390	5	75	1/61	61
352AA022303WD0	22	7/8	30	4	420	5	75	1/61	61
352AA025333WD0	25	1	33	4	470	5	75	1/61	61
352AA028363WD0	28	1 1/8	36	4	520	5	75	1/61	61
352AA030383WD0	30	1 3/16	38	4	550	5	75	1/61	61
352AA032403WD0	32	1 1/4	40	4	580	5	75	1/61	61
352AA035433WD0	35	1 3/8	43	4	620	5	75	1/61	61
352AA038483WD0	38	1 1/2	48	5	860	5	75	1/61	61
352AA040503WD0	40	1 9/16	50	5	890	5	75	1/61	61
352AA042523WD0	42	1 5/8	52	5	930	5	75	1/61	61
352AA045553WD0	45	1 3/4	55	5	990	5	75	1/61	61
352AA048583WD0	48	1 7/8	58	5	1050	5	75	1/61	61
352AA051613WD0	51	2	61	5	1120	5	75	1/61	61
352AA055653WD0	55	2 3/16	65	5	1190	5	75	1	1
352AA057673WD0	57	2 1/4	67	5	1230	5	75	1	1
352AA060703WD0	60	2 3/8	70	5	1290	5	75	1/61	61
352AA063733WD0	63	2 1/2	73	5	1350	5	75	1	1
352AA070803WD0	70	2 3/4	80	5	1450	5	75	1	1
352AA076863WD0	76	3	86	5	1560	5	75	1	1
352AA080903WD0	80	3 1/8	90	5	1650	5	75	1	1
352AA090023WD0	90	3 9/16	102	6	2020	5	75	1	1
352AA102143WD0	102	4	114	6	2270	5	75	1	1
352AA110223WD0	110	4 5/16	122	6	2420	5	75	1	1