

T-750 AA  
 喷砂管 10 bar (150 psi)



内胶层: 黑色导电 NR - 耐磨损

加强层: 两层高强度纤维线

外胶层: 黑色导电 SBR/NR - 耐磨损、耐臭氧 - 刺孔工艺

应用: 喷砂

安全系数: 3:1

温度范围: -30 °C +80 °C (-22 °F +176 °F)

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
750AA019337R03	19	3/4	33	7	670	10	150			30,5/40	40
750AA019357R03	19	3/4	35	8	790	10	150			40	
750AA019387R03	19	3/4	38	9,5	930	10	150			15,25/30,5/40	
750AA025407R03	25	1	40	7,5	820	10	150			30,5/40	40
750AA025487R03	25	1	48	11,5	1440	10	150			15,25/30,5/40	
750AA032487R03	32	1 1/4	48	8	1180	10	150			30,5/40	40
750AA032557R03	32	1 1/4	55	11,5	1730	10	150			15,25/30,5/40	
750AA038557R03	38	1 1/2	55	8,5	1540	10	150			30,5/40	40
750AA038607R03	38	1 1/2	60	11	1960	10	150			15,25/30,5/40	
750AA040607R03	40	1 9/16	60	10	1800	10	150			40	40
750AA051717R03	51	2	71	10	2210	10	150			30,5/40	40
750AA051737R03	51	2	73	11	2490	10	150			15,25/30,5/40	