

T-340 AA

蒸气管 18 bar (270 psi) 钢丝编织

NFT 47263 CAT I TYPE 3

BS5342/2 CLASS A DIN 2825



内胶层:黑色导电EPDM

加强层:两层高强度钢丝编织

外胶层:黑色导电EPDM -耐热、耐磨损、耐臭氧-刺孔工艺

应用:饱和或过热水蒸气

安全系数: 10:1

温度范围: -40 °C +210 °C (-40 °F +410 °F)

瞬间可承受最高温度232 °C (450 °F)

| Code | ID mm | ID inch | OD mm | Wall mm | Weight g/m | WP bar | WP psi | Vac. % | BR mm | Available Length m | Stock Length m |
|----------------|----------|------------|----------|------------|---------------|-----------|-----------|-----------|----------|-----------------------|-------------------|
| 340AA013253YG3 | 13 | 1/2 | 25 | 6 | 590 | 18 | 270 | | 130 | 15,25/30,5 | 30,5 |
| 340AA016283YG3 | 16 | 5/8 | 28 | 6 | 660 | 18 | 270 | | 160 | 30,5 | |
| 340AA019323YG3 | 19 | 3/4 | 32 | 6,5 | 780 | 18 | 270 | | 190 | 15,25/30,5 | 30,5 |
| 340AA025383YG3 | 25 | 1 | 38 | 6,5 | 960 | 18 | 270 | | 250 | 15,25/30,5 | 30,5 |
| 340AA032463YG3 | 32 | 1 1/4 | 46 | 7 | 1230 | 18 | 270 | | 320 | 30,5 | |
| 340AA038523YG3 | 38 | 1 1/2 | 52 | 7 | 1440 | 18 | 270 | | 380 | 30,5 | |
| 340AA051673YG3 | 51 | 2 | 67 | 8 | 2280 | 18 | 270 | | 510 | 30,5 | |