

// 253AA



EVOLUTION

排水 10 bar (150 psi) 可扁平

内胶层: 黑色EPDM

加强层: 高强度纤维线

外胶层: 黑色EPDM - 耐磨损、耐臭氧

应用: 可扁平排水软管

常规运行温度范围: -30°C +80°C (-22°F +176°F)

Ø		Ø		Ø		Ø		Ø		Ø		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
32,0	1 1/4"	40,00	1,57	10	150	30	450				0,460	0,31
38,0	1 1/2"	46,00	1,81	10	150	30	450				0,550	0,37
51,0	2"	59,00	2,32	10	150	30	450				0,750	0,51
63,0	2 1/2"	71,00	2,80	10	150	30	450				0,910	0,62
76,0	3"	86,00	3,39	10	150	30	450				1,490	1,01
102,0	4"	112,00	4,41	10	150	30	450				2,040	1,38
127,0	5"	139,00	5,47	10	150	30	450				2,740	1,85
152,0	6"	164,00	6,46	10	150	30	450				3,370	2,27
203,0	8"	217,00	8,54	10	150	20	300				4,810	3,24
254,0	10"	270,00	10,63	10	150	20	300				7,680	5,17