

// 202AA



EVOLUTION

一般用途吸排 10 bar (150 psi) – EPDM

内胶层: 黑色导电EPDM

加强层: 高强度纤维线并嵌有螺旋钢丝

外胶层: 黑色导电EPDM - 耐磨损、耐臭氧

应用: 吸排水

也适用于一般工业, 农业的中性化学品和化肥的应用

常规运行温度范围: -40°C +100°C (-40°F +212°F)

取决于输送的化学品

↻		↻		↻		↻		↻		↻	↻	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
25,0	1"	36,00	1,42	10	150	30	450	50	1,97	100	0,700	0,48
32,0	1 1/4"	43,00	1,69	10	150	30	450	64	2,52	100	0,860	0,58
38,0	1 1/2"	49,00	1,93	10	150	30	450	76	2,99	100	1,000	0,68
51,0	2"	62,00	2,44	10	150	30	450	102	4,02	100	1,300	0,88
63,0	2 1/2"	76,00	2,99	10	150	30	450	189	7,44	90	2,010	1,36
76,0	3"	89,00	3,50	10	150	30	450	228	8,98	90	2,390	1,61
102,0	4"	116,00	4,57	10	150	30	450	306	12,05	90	3,300	2,22
152,0	6"	168,00	6,61	10	150	25	375	608	23,94	80	5,330	3,59
203,0	8"	221,00	8,70	10	150	25	375	812	31,97	70	9,880	6,64
254,0	10"	272,00	10,71	10	150	25	375	1270	50,00	60	13,520	9,09