

// 650AA



EVOLUTION

燃油输送 10 bar (150 psi)

内胶层: 黑色导电NBR

加强层: 高强度纤维线

外胶层: 黑色导电CR - 耐磨损、耐臭氧、耐烃类化合物和耐火

应用: 一般用途的燃油输送

常规运行温度范围: -30° C +80° C (-22° F +176° F)

↔		→		↓		↙		↘		⌋	⌌	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
19,0	3/4"	29,00	1,14	10	150	30	450				0,440	0,30
25,0	1"	35,00	1,38	10	150	30	450				0,560	0,38
32,0	1 1/4"	42,00	1,65	10	150	30	450				0,690	0,47
32,0	1 1/4"	44,00	1,73	10	150	30	450				0,810	0,55
38,0	1 1/2"	48,00	1,89	10	150	30	450				0,800	0,54
38,0	1 1/2"	50,00	1,97	10	150	30	450				0,950	0,64
51,0	2"	61,00	2,40	10	150	30	450				1,050	0,71
51,0	2"	63,00	2,48	10	150	30	450				1,230	0,83
63,0	2 1/2"	75,00	2,95	10	150	30	450				1,430	0,97
76,0	3"	88,00	3,46	10	150	30	450				1,920	1,30
102,0	4"	114,00	4,49	10	150	30	450				2,600	1,75