



特殊类液压软管

应用:

高压管工作压力达到345bar。

适用于可增加耐磨的天然气管，防静电。真空度：28英寸水银柱。

应用标准:

Exitflex QD-M; NFPA 52

结构:

内层: 尼龙

加强层: 一层编织芳纶，一层编织电导纤维。

外层: 红色，针扎-聚氨酯。用两条或多条不同尺寸的管线组成。特殊颜色及印刷要求请咨询制造商

温度范围:

-40 °C bis +80 °C

EF 324

CNG Gas hose



Special hydraulic hoses

Application:

High Pressure Hose up to 345 bar. Suitable for compressed natural gas (CNG) application with increased resistance to abrasion. Dissipates static build up. Vacuum: 28 inch Hg

Application Standards:

Exitflex QD-M, NFPA 52

Construction:

Inner tube: Nylon

Reinforcement: **EF324** - two or more Braids of Synthetic fiber with electrically conductive layer,

EF325 - two or more Braids of Aramid fiber with single braid of steel wire (EF325)

Cover: Polyurethane, red colour, pin pricked. Available twin and multi lines with different hose combination and sizes. Special colour and private print up on request.

Temperature Standards:

-40°C to + 80°C

EF 325

CNG Gas hose



Hose Type	Size	Hose I.D. (Nom.)	Hose O.D. (Nom.)		Working Pressure		Min. Burst Pressure		Min. Bend Radius			
Ref.-Nr.	Dash Size	DN	in inch	in mm	in inch	in mm	in psi	in bar	in psi	in bar	in mm	in inch
EF324-4	4	6	1/4	6,4	0,630	16,0	5.000	345	20.000	1.380	51	2,0
EF324-6	6	10	3/8	9,5	0,770	19,6	4.000	275	16.000	1.100	64	2,5
EF325-3	3	5	3/16	4,8	0,460	11,7	7.250	500	29.000	2.000	38	1,5
EF325-4	4	6	1/4	6,4	0,550	14,0	7.250	500	29.000	2.000	70	2,8
EF325-6	6	10	3/8	9,6	0,710	18,0	5.000	345	20.000	1.380	100	4,0
EF325-8	8	12	1/2	12,8	0,830	21,1	5.000	345	20.000	1.380	180	7,1
EF325-12	12	19	3/4	19,0	1,150	29,2	5.000	345	20.000	1.380	250	9,8
EF325-16	16	25	1	25,0	1,480	37,5	5.000	345	20.000	1.380	254	10,0