

Oil Hose

油管

Application : Hydraulic systems using petroleum or water base fluids such as light fuel oil , crude oil, general gasoline discharge, gasoline curb-pump

Construction

Tube: Synthetic rubber

Cover: Synthetic rubber

Reinforcement: Multiple textile braid

Temp.Range: -30 °C to + 80°C

Burst Pressure(B.P.): Working Prssure(W.P.) x 4

用途

液壓系統配管用, 輸送液壓油, 燃料油, 潤滑油, 重油等為協機公司表性油管產品

構造

內管層: 耐油性佳之合成橡膠配方

外管層: 耐油, 耐候之特殊橡膠配方

補強層: 適合夾合之纖維編織補強

適用溫度: -30 °C 到 +80°C

爆破壓力: 為最高使用壓力的4倍

產品編號 part no.	I.D. 內徑		braid 編織	Wall thickness 管壁厚 mm	W.P. 最高使用壓力		Length 長度 M 公尺
	inch	mm			psi	kgf/cm ²	
MO 0151	3/16	4.8	1	2.8	200	14	100
MO 0152	3/16	4.8	2	2.8	250	18	100
MO 0201	1/4	6.3	1	3.0	200	14	100
MO 0202	1/4	6.3	2	3.0	300	21	100
MO 0251	5/16	7.9	1	3.0	200	14	100
MO 0252	5/16	7.9	2	3.0	300	21	100
MO 0301	3/8	9.5	1	3.0	200	14	100
MO 0302	3/8	9.5	2	3.0	300	21	100
MO 0401	1/2	12.7	1	3.5	200	14	100
MO 0402	1/2	12.7	2	3.5	250	18	100
MO 0403	1/2	12.7	3	3.5	300	21	100
MO 0501	5/8	15.9	1	3.5	150	11	100
MO 0502	5/8	15.9	2	3.5	250	18	100
MO 0503	5/8	15.9	3	3.5	300	21	100
MO 0601	3/4	19.1	1	4.0	120	8	100
MO 0602	3/4	19.1	2	4.0	250	18	100
MO 0603	3/4	19.1	3	4.0	300	21	100
MO 1001	1	25.4	1	4.0	120	8	100
MO 1002	1	25.4	2	4.0	200	14	100
MO 1003	1	25.4	3	4.0	250	18	100
MO 1202	1- 1/4	31.8	2	5.0	170	12	30
MO 1203	1- 1/4	31.8	3	5.0	200	14	30
MO 1402	1-1/2	38.1	2	6.0	170	12	30
MO 1403	1-1/2	38.1	3	6.0	200	14	30
MO 1502	1-5/8	41.3	2	6.0	120	8	30
MO 1503	1-5/8	41.3	3	6.0	150	11	30
MO 1602	1-3/4	44.5	2	6.0	170	12	30
MO 1603	1-3/4	44.5	3	6.0	200	14	30
MO 2002	2	50.8	2	6.0	170	12	30
MO 2003	2	50.8	3	6.0	200	14	30