

## S-267 BE

泥水吸排管 - PVC - 中等工况

超弹性



结构: 灰色 PVC 带有蓝色螺旋条纹 - 耐磨损、耐臭氧加强层-白色抗震硬质 PVC

应用: 吸水和排水。适用于泥浆灌装车, 低温时具有好的柔性

安全系数:3:1

温度范围: -20 °C +60 °C (-4 °F +140 °F)

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
267BE025002S50	25	1			410	7	100	90	100	50	50
267BE032002S50	32	1 1/4			600	7	100	90	128	50	50
267BE038002S50	38	1 1/2			700	7	100	90	152	20/50	50
267BE051002S50	51	2			1000	5	75	90	204	20/50	50
267BE060002S50	60	2 3/8			1280	5	75	90	240	50	50
267BE063002S50	63	2 1/2			1340	5	75	90	252	50	50
267BE076002S50	76	3			1750	5	75	90	304	20/50	50
267BE080002S50	80	3 1/8			1840	5	75	90	320	30/50	50
267BE090002S50	90	3 9/16			2260	4	60	90	360	30	30
267BE102002S50	102	4			2700	4	60	90	408	20/30	30
267BE110002S50	110	4 5/16			3100	4	60	80	440	20	20
267BE120002S50	120	4 3/4			3600	4	60	80	480	20	20
267BE127002S50	127	5			3800	4	60	80	508	20	20
267BE152002S50	152	6			4850	3	45	80	608	20	20
267BE203002S50	203	8			9100	3	45	60	812	10	10