

S-472 OO

一般用途食品安全认证吸排管 - PVC

FDA - EU 10/2011 A+B+C - AS 2070



具有不含邻苯二甲酸酯等塑化剂的认证

结构: 透明 PVC - 耐磨损、耐臭氧

加强层: 螺旋钢丝应用: 一般用途 - 液态食品和酒精度不超过 20% 的酒精饮料的吸排用 5% 的苏打水消毒

安全系数: 3:1

温度范围: -5 °C +60 °C (+23 °F +140 °F)

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
472OO010164LK0	10	3/8	16	3	170	15	225	90	40	60	60
472OO013194LK0	13	1/2	19	3	205	7	100	85	52	60	60
472OO014204LK0	14	9/16	20	3	220	6	90	85	56	60	60
472OO016224LK0	16	5/8	22	3	250	6	90	85	64	60	60
472OO018264LK0	18	11/16	25	3,5	320	6	90	85	72	60	60
472OO020284LK0	20	13/16	26	3	340	5	75	85	80	60	60
472OO022304LK0	22	7/8	29	3,5	380	5	75	85	88	60	60
472OO025334LK0	25	1	33	4	530	5	75	85	100	60	60
472OO030384LK0	30	1 3/16	38	4	620	4	60	85	120	60	60
472OO032404LK0	32	1 1/4	40	4	655	4	60	85	128	60	60
472OO035454LK0	35	1 3/8	44	4,5	800	4	60	85	140	60	60
472OO038484LK0	38	1 1/2	47	4,5	855	4	60	85	152	30	30
472OO040504LK0	40	1 9/16	49	4,5	895	3	45	85	160	30	30
472OO045554LK0	45	1 3/4	55	5	1100	3	45	80	180	30	30
472OO051614LK0	51	2	61	5	1230	3	45	80	204	30	30
472OO060724LK0	60	2 3/8	72	6	1700	2	30	80	240	30	30
472OO063754LK0	63	2 1/2	75	6	1775	2	30	80	252	30	30
472OO070844LK0	70	2 3/4	84	7	2030	2	30	80	280	30	30
472OO076904LK0	76	3	90	7	2450	2	30	70	304	30	30
472OO080944LK0	80	3 1/8	94	7	2565	2	30	70	320	30	30
472OO090044LK0	90	3 9/16	104	7	3000	2	30	70	360	30	30
472OO102164LK0	102	4	116	7	3480	2	30	70	408	30	30
472OO152724LK0	152	6	172	10	7300	2	30	70	608	20	20