

# EF 614

回油管 20 Bar

Oil Suction and Delivery Hose

W.P. 20 BAR(300PSI)

在冬季或夏季，完全真空情况下，在石油管道分配站，耐耗吸排油管用来处理油罐车里不同等级含量少于 50%的汽油或石油芳炷。

#### 应用标准:

Exitflex QD-M, 高于 ISO 1307

#### 结构:

内层: NBR

加强层: 多层螺旋钢丝合成纤维层

外层: NR/EPDM 混合物, 黑色芯棒, 缠绕定型: 耐侵蚀, 耐油, 耐老化, 耐磨损

标记: 红色条纹/黑色文字

#### 温度范围:

-20°C ~ 80°C

#### Oil suction and delivery hose

#### Application:

Mandrel built heavy duty oil suction and delivery hose for handling grades of gasoline or petroleum oils of aromatic content up to 50% from tank truck, in dispensing station, etc during winter/summer seasons, and withstands full vacuum.

#### Application Standards:

Exitflex QD-M, exceeding ISO 1307

#### Construction:

Core: NBR Blended

Reinforcement: Plies of synthetic cords with helix wire.

Cover: NBR/EPDM Blended, black mandrel, wrapped type, weather, oil, ozone, abrasion resistant.

Marking: Red stripe/Black text.

#### Temperature Standards:

-20°C to + 80°C



软管型号 Hose Type	内径 Hose I.D.		外径 Hose O.D.	工作压力 Working Pressure		最小爆破压力 Min.Burst Pressure		重量 Weight
	英寸	毫米		Psi	Bar	Psi	Bar	
EF614-12	3/4	19	29	300	20.0	870	60.0	0.73
EF614-16	1	25	35	300	20.0	870	60.0	0.88
EF614-20	1 1/4	32	42	300	20.0	870	60.0	1.16
EF614-24	1 1/2	38	48	300	20.0	870	60.0	1.40
EF614-32	2	51	63	300	20.0	870	60.0	1.81
EF614-40	2 1/2	63	77	300	20.0	870	60.0	2.50
EF614-48	3	76	90	300	20.0	870	60.0	3.12
EF614-56	3 1/2	89	104	300	20.0	870	60.0	3.55
EF614-64	4	102	118	300	20.0	870	60.0	4.77
EF614-80	5	127	143	300	20.0	870	60.0	8.65
EF614-96	6	152	172	300	20.0	870	60.0	11.75