



缠绕管

应用:

高压缠绕管工作压力达到 420bar，外径层致密。在液压系统中介质是液压油、水基合成物或水，适用于农业，建筑，材料处理设备以及机械等。

应用标准:

EN856-4SH

结构:

内层: 耐油和水的合成橡胶

加强层: 四层高强度缠绕钢丝

外层: 黑色合成橡胶，耐油，耐老化，耐磨损

温度范围:

-40°C ~ 121°C

液压胶管

Hydraulic Hose

EN856-4SH



Multispiral Hose

Application:

High pressure hydraulic line up to 420 bar and requires compact outer dia. for use with petroleum, synthetic or water based fluids in hydraulic systems. Suitable for agricultural, construction, material handling equipment and machinery.

Application Standards:

EN856-4SH

Construction:

Core: Oil and Water resistant Synthetic rubber

Reinforcement: Four high tensile steel wire spirals

Cover: Black color, Synthetic rubber resistant to oil, weather, Ozone and abrasion.

Temperature Standards:

-40°C bis + 121°C



软管型号 Hose Type	尺寸 Size		内径 Hose I.D.		编织层外径 Braid O.D.		外径 Hose O.D.		工作压力 Working Pressure		最小爆破压力 Min.Burst Pressure		最小弯曲半径 Min.Bend Radius	
	线后数字	公称通径	英寸	毫米	英寸	毫米	英寸	毫米	Psi	Bar	Psi	Bar	毫米	英寸
4SH-12-S4	12	20	3/4	19.1	1.12	28.4	1.26	31.9	6,090	420	24,360	1,680	280	11.00
4SH-16-S4	16	25	1	25.4	1.39	35.2	1.51	38.3	5,510	380	22,040	1,520	340	13.40
4SH-20-S4	20	32	1 ¹ / ₄	32.0	1.67	42.3	1.77	44.9	4,710	325	18,850	1,300	460	18.10
4SH-24-S4	24	38	1 ¹ / ₂	38.0	1.92	48.8	2.08	52.9	4,205	290	16,820	1,160	560	22.05
4SH-32-S4	32	50	2	51.0	2.49	63.2	2.66	67.5	3,625	250	14,500	1,000	700	27.55