

// R8 船用软管



船用高压液压管 140 bar ~420 bar (2000 psi~6000 psi)

内胶层: 耐油 (包括可耐生物降解液压油) 树脂

加强层: 高强度芳纶纤维编织

外胶层: 耐油、耐海水和耐臭氧的聚氨酯, 表面刺孔

应用: 船用和海工设备, 吊机, 航运系统。海洋地震勘探作业。也推荐用于高湿度环境下的陆上设备。符合或超越 SAE 100 R8 标准

安全系数: 4:1

常规运行温度范围: -40 ° C +100 ° C (-40 ° F +212° F)

对于空气和水基流体温度限制于70°C (+158° F)

推荐接头:

- AISI 316 SS; NPTF公接头; JIC公接头和母接头

										
mm	in	mm	in	bar	psi	mm	in	%	kg/m	lb/ft
-3	5	3/16	8,9	0,35	35,0	5000	30	1,18	0,050	0,035
-4	6,5	1/4	11,5	0,453	35,0	5000	50	1,97	0,080	0,055
-5	8,1	5/16	13,4	0,528	30,0	4300	55	2,17	0,105	0,075
-6	9,7	3/8	15,5	0,61	28,0	4000	60	2,36	0,130	0,090
-8	13	1/2	19,9	0,783	24,5	3500	80	3,15	0,195	0,135
-10	16,3	5/8	23,4	0,921	20,0	2900	125	4,92	0,245	0,165
-12	19,5	3/4	26,9	1,059	16,5	2300	150	5,91	0,310	0,210
-16	25,9	1	34,2	1,346	14,0	2000	200	7,87	0,425	0,290