

// 655AA



燃油输送管 16 bar (240 psi)

优于 EN 1761 - TRbF 131/2

内胶层: 黑色导电NBR

加强层: 高强度纤维线

外胶层: 黑色导电CR – 耐磨损、耐臭氧、耐烃类化合物和耐火

应用: 燃油输送

在恶劣工况下具有超长的使用寿命

常规运行温度范围: -30 ° C +70 ° C (-22 ° F +158 ° F)

推荐接头:

- 带预扣压套筒的NPT外螺纹的软管接头
- ASA150标准的固定法兰或松套法兰软管接头
- 液压接头, 请参考ALFAGOMMA液压产品目录

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
19,0	3/4"	31,00	1,22	16	240	48	720	125,0	4,92		0,560	0,38
25,0	1"	37,00	1,46	16	240	48	720	150,0	5,91		0,690	0,47
32,0	1 1/4"	44,00	1,73	16	240	48	720	175,0	6,89		0,870	0,59
38,0	1 1/2"	51,00	2,01	16	240	48	720	225,0	8,86		1,020	0,69
51,0	2"	67,00	2,64	16	240	48	720	275,0	10,83		1,550	1,05
63,0	2 1/2"	79,00	3,11	16	240	48	720	300,0	11,81		1,880	1,27
76,0	3"	92,00	3,62	16	240	48	720	350,0	13,78		2,310	1,56
102,0	4"	118,00	4,65	16	240	48	720	450,0	17,72		3,410	2,30
152,0	6"	170,00	6,69	16	240	48	720	750,0	29,53		5,140	3,46