

											
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
25	1	35	1,38	10	150	50	2,00	100	0,730	0,495	
32	1 1/4	42	1,65	10	150	64	2,50	100	0,900	0,605	
38	1 1/2	48	1,89	10	150	76	3,00	100	1,040	0,700	
40	1 9/16	50	1,97	10	150	80	3,00	100	1,090	0,735	
42	1 5/8	52	2,05	10	150	88	3,50	100	1,130	0,760	
51	2	61	2,40	10	150	100	4,00	100	1,420	0,955	
63	2 1/2	75	2,95	10	150	126	5,00	100	2,010	1,355	
76	3	88	3,46	10	150	228	9,00	90	2,590	1,745	
102	4	116	4,57	10	150	306	12,00	90	3,850	2,590	
NA		LA		NEU		EMEA		SA		AP	AU



412LE

奶罐车软管 10 bar (150 psi) - 硬壁 FDA arrêté du 09/11/94 A

内胶层: 白色 NR

加强层: 两层高强度纤维线并嵌有螺旋钢丝

外胶层: 蓝色 NR/EPDM - 耐磨损、耐臭氧

应用: 液态食品吸排, 该软管具有卓越的柔性, 适合奶罐车用 5% 的苏打水消毒

安全系数: 3:1

温度范围: -40 °C +80 °C (-40 °F +176 °F)

