

**HYDRAULIC HOSE DIVISION
ALFAGOMMA GROUP****DECLARATION OF
CONFORMITY**

DATE: 12/06/2024

**HIGH PRESSURE HYDRAULIC LINES, FUEL OIL, ANTIFREEZE SOLUTIONS, AIR AND
WATER.****TEMPERATURE -40 °C +100 °C (-40 °F +212 °F), AIR MAX T = +70 °C (+160 °F)****AG FLEXOR 1SN/R1AT MINETUFF**

APPLICATION:	HIGH PRESSURE HYDRAULIC LINES, FUEL OIL, ANTIFREEZE SOLUTIONS, AIR AND WATER.
TUBE:	OIL RESISTANT SYNTHETIC RUBBER.
REINFORCEMENT:	ONE HIGH TENSILE STEEL BRAID (1B).
COVER:	ABRASION, OZONE AND HYDROCARBON RESISTANT SYNTHETIC RUBBER.
STANDARD BRAND:	<AG> ALFAGOMMA FLEXOR 1AT/1SN _ MSHA-..
NORMS:	SAE 100 R1AT – UNI EN 853 1SN - ALFAGOMMA

TECHNICAL DATA

Product Code	Internal Diameter (mm)	Outside Diameter (mm)	Max Working Pressure (Mpa)	Minimum Burst Pressure (MPa)	Minimum Bend Radius (mm)	Weight (kg/m)
8T4AA06378IEB8	63,3~64,9	< 78.1	3,5	14,0	740	2,720
8T4AA07690IEB8	76,0~77,6	< 91,0	2,5	10,0	880	3,240

**WE HEREBY DECLARE THAT THE GOODS SUPPLIED CONFORM TO STANDARD NORMS
REQUIREMENT.**

(NORIZAM MOHD SALLEH)

FACTORY QUALITY MANAGER

上海沅峻流体科技有限公司 - AG授权分销商

TEL: +86-21-58400374/58400394

FAX: +86-21-50182690

E-mail: fengjunfluid@163.com

ADD: 上海市奉贤区浦卫公路6655号一号厂房

<https://tiger-flex.com.cn/>**ALFAGOMMA MALAYSIA SDN BHD**

PLO 344, JALAN PERAK 4, PO BOX 97, 81707 PASIR GUDANG, JOHOR, MALAYSIA

TEL (60) 251 0852 – FAX (60) 251 0408

E-mail: alfagomma@alfagomma.com.my